



Service with Energy.

# HOS BEIGNET

## S240E Offshore Supply Vessel



### DIMENSIONS AND REGULATORY INFORMATION

<b>Length:</b>	240 ft 0 in (73.2 m)	<b>Beam:</b>	56 ft 0 in (17.1 m)	<b>Draft Max:</b>	15 ft 0 in (4.57 m)
<b>Gross:</b>	1,809 GT	<b>Net :</b>	555 NT	<b>Draft Min:</b>	9 ft 0 in (2.74 m)
<b>IMO:</b>	9240184	<b>O.N.:</b>	1097129	<b>Flag:</b>	U.S.
<b>Certifications:</b>	Oceans-SOLAS, USCG Subchapter L				
<b>Classifications:</b>	Loadline, American Bureau of Shipping, +DPS-2, (E), +A1, +AMS, OSV				

### PERFORMANCE

<b>Max Speed:</b>	12.0 kts	150 gal/hr (568 l/hr)
<b>Cruise Speed:</b>	10.0 kts	125 gal/hr (473 l/hr)

### PROPULSION, MACHINERY AND STEERING

<b>Main Engines:</b>	2 x Caterpillar 3516B	<b>Total Horsepower:</b>	4,000 hp
<b>Propellers:</b>	FPP, 5 Blade	<b>Propeller Diameter:</b>	105in (2,667mm)
<b>Primary Generators:</b>	2 x Caterpillar 3306 B	<b>Total Rating:</b>	340 kW
<b>Bow Thruster:</b>	2 x Brunvoll CPP Tunnel	<b>Total Horsepower:</b>	1,900 hp
<b>Stern Thruster:</b>	1 x Brunvoll CPP Tunnel	<b>Total Horsepower:</b>	950 hp
<b>Rudder:</b>	Air-foil, Independent Steering	<b>Power Generation:</b>	480V/60 Hz/3-Phase

### CAPACITIES AND DELIVERY RATES

<b>Deadweight:</b>	2,772 LT (2,816 MT)	<b>Deck Area:</b>	170ft x 45ft (7,650ft <sup>2</sup> ) 51.8m x 13.7m (710.7m <sup>2</sup> )
<b>Deck Cargo:</b>	1,750 LT (1,778 MT)	<b>Deck Load Rating:</b>	1,000 lbs/ft <sup>2</sup> (5 MT/m <sup>2</sup> )
<b>Dry Bulk:</b>	8,000 ft <sup>3</sup> (226 m <sup>3</sup> )	<b>System Pressure:</b>	80 psi (5.5 bar)
<b>Brine:</b>	8,000 bbl (1,272 m <sup>3</sup> )	<b>Discharge Rate:</b>	800 GPM (182 m <sup>3</sup> /hr)
<b>Liquid Mud:</b>	8,000 bbl (1,272 m <sup>3</sup> )	<b>Discharge Rate:</b>	800 GPM (182 m <sup>3</sup> /hr)
<b>Potable Water:</b>	32,400 gal (123 m <sup>3</sup> )	<b>Discharge Rate:</b>	800 GPM (182 m <sup>3</sup> /hr)
<b>Rig Fuel:</b>	135,400 gal (512 m <sup>3</sup> )	<b>Discharge Rate:</b>	800 GPM (182 m <sup>3</sup> /hr)
<b>Rig Water:</b>	294,670 gal (1,115 m <sup>3</sup> )	<b>Discharge Rate:</b>	800 GPM (182 m <sup>3</sup> /hr)
<b>Cooler Area:</b>	300 ft <sup>3</sup> (8 m <sup>3</sup> )	<b>Freezer Area:</b>	300 ft <sup>3</sup> (8 m <sup>3</sup> )

### ELECTRONICS

Auto Pilot, C-Nav, Depth Sounder, DGPS w/AIS, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, Navtex, Public Phone System w/loudhailer, Radar, SARTs, Single Side Band, VHF Radio, VHF Radio (Handheld), Windbird, Cyscan, Kongsberg K-POS

### ACCOMMODATIONS

10 air conditioned/heated staterooms certified for 20 person berthing.

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.